

Cámara tipo Bullet **HD-LBQ24S300** Exterior

Camera

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
--------------	--

Resolution	3MP
------------	-----

Effective Pixels	2065(H)*1553(V)
------------------	-----------------

Compression	H.264/H.265/JPEG/AVI/MJPEG
-------------	----------------------------

TV System	PAL/NTSC
-----------	----------

Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
-------------------------	---

S/N Ratio	≥52dB
-----------	-------

Scanning System	Progressive
-----------------	-------------

Video Output	Network
--------------	---------

Reset Button	Optional
--------------	----------

Lens

Focus Length	3.6mm (2.8mm/6mm Optional)
--------------	----------------------------

Focus Control	Fixed
---------------	-------

Lens Type	Fixed
-----------	-------

Pixels	4MP
--------	-----

Night Vision

Infrared LED	14 μ x 18PCS
--------------	------------------

Infrared Distance	20M
-------------------	-----

IR Status	Under 10 Lux By CDS
-----------	---------------------

IR Power On	CDS Auto Control
-------------	------------------

Network

Ethernet	RJ-45 (10/100Base-T)
----------	----------------------

Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
----------	---

ONVIF	Support ONVIF 2.4
-------	-------------------

P2P	YES, Support QR Code
-----	----------------------

POE	Optional, Support IEEE 802.3af
-----	--------------------------------

Video Delay	0.3S (Within the Lan)
-------------	-----------------------

Main Stream 1	2048*1536@30fps
Main Stream 2	1920*1080@30fps
Main Stream 3	/
Sub Stream 1	720*480@30fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari

Smart Phone	iPhone, iPad, Android, Android Pad
-------------	------------------------------------

Camera Features

Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Starlight	/
Corridor Pattern	Support
Defog Mode	Support
ROI	/
BLC	Support
HDR	Support

WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands

Interface

Audio	Optional
Alarm	/
SD Card Slot	/
RS485	/

General

Housing	Metal ,IP66
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 850mA
Dimension	151(W) x 64(H) x 65.5(D)mm
Weight	700g