



Model	PT6A122
<b>Camera</b>	
Image Sensor	1/3" Super HAD II SONY CCD, Effio
Horizontal Resolution	700TVL
S/N Ratio	>55db
<b>PTZ</b>	
Horizontal Rotation Speed	200°/s
Tilt Rotation Speed	100°/s
Horizontal Rotation Range	360°
Tilt Rotation Range	93°
Auto Flip	Horizontal 180°, Vertical 90°
A-B Scan	User programmable
A-B Scan Speed	1-9 speed setting available
360° Scan Speed	1-9 speed setting available
Dwell Preset	5-60s interval
Preset Points	220
Go to Preset Speed	200°/s
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
Pattern Scan	4 pcs
Pattern Scan Record	max.15 minutes, max.512 commands
Park Action	Home position, 360° scan/A-B scan/guard tour 1-3
Home Pos Time	1-60mins available
PWR on Action	Memory as power off/360° scan/A-B scan/Preset cruise1-3
<b>Auxiliary Interface</b>	
Communication Protocol	Pelco-D,Pelco-P
Communication	RS485 Bus
Baud Rate	1200/2400/4800/9600bps
<b>General</b>	
Operating Temperature	Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Auto Control IR LED	PWM
OSD Menu	English
IR Illumination Distance	50M
Power	DC12V ≤4A
Consumption	≤ 20W
Lightning Protection	Transient voltage 6000V
Dimension	28x32x20(cm)
Weight	3.4kgs