

# NVR9808AT

## System

Main Processor ARM Cortex A7 Quad-core Processor

Operating System Embedded LINUX

## Video

Input 16CH (4096×2160, 2592×1944, 2048×1536, 1920×1080, 1280×960, 1280×720, etc), Incoming Bandwidth: 80MB

Output 1 VGA, 1 HDMI

## Audio

Input 1 Port RCA

Output 1 Port RCA

## Alarm

Sensor Input NO

Output NO

Motion Detection 16 channel

Email Alarm Support

## Display

VGA Resolution: 1920×1080/1280×1024/1280×720

HDMI Resolution: 4K 3840×2160/1920×1080/1280×1024/1280×720

Display Split 16CHxD1/9CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP/1CHx4k

Digital Zoom YES

OSD Camera Title, Time, Video Loss, Recording, Motion Detection

## Recording

Video Compression H.265/H.264

Resolution 4k(4096×2160), 5MP(2592×1944), 4MP(2688×1520), 3MP(2048×1536), 1080P(1920×1080), 960P(1280×960), 720P(1280×720), D1 (704×576/704×480)

PAL :4k@8×25fp,5MP@12×25fp,4MP@15×25fp,3MP@16×25fp,1080P@16×25fp, 960P@16×25fp,720P@16×25fp, D1@16×25fp

Record Rate NTSC: 4k@8×30fp,5MP@12×30fp,4MP@15×30fp,3MP@16×30fp,1080P@16×30fp, 960P@16×30fp, 720P@16×30fp, D1@16×30fp

Record Mode Manual\Timer\Motion Detection

## Hard Disk Driver

Interface Type 2 SATA Interface

Capacity Up to 12TB capacity

## General

Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa

Language German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek

USB Interface 2 USB 2.0 Interfaces

Power Supply DC48V/2500mA ≤10W (Without Hard Disk and POE)

Working Environment -10~55°C/10~90%

