



SPECIFICATION	
Model	XVR3132L
System	
Main Processor	HI3531A
Operating System	Embedded LINUX
Video	
Input	Analog: 32*1080N Analog+Network: 30*Analog(1080N)+2*network(Max 8MP), 28*Analog(1080N)+4*network(Max 8MP), 26*Analog(1080N)+6*network(Max 8MP), 24*Analog(1080N)+8*network(Max 8MP), 22*Analog(1080N)+10*network(Max 8MP), 20*Analog(1080N)+12*network(Max 8MP), 18*Analog(1080N)+14*network(Max 8MP), 16*Analog(1080N)+16*network(Max 8MP) 14*Analog(1080N)+18*network(Max 8MP), 12*Analog(1080N)+20*network(Max 8MP),10*Analog(1080N)+22*network(Max 8MP) 8*Analog(1080N)+24*network(Max 8MP), 6*Analog(1080N)+26*network(Max 8MP), 4*Analog(1080N)+28*network(Max 8MP) 2*Analog(1080N)+30*network(Max 8MP) Network: 32*network(Max 8MP)(Total incoming bandwidth ≤160M)
Input	32CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/Network
Output	1HDMI,1 VGA, 1CVBS
Audio	
Input	12 Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
Alarm	
Sensor Input	16 Channel
Output	4 Channel
Motion Detection	32 Channel
Trigger Events	Recording, Alarm, Email, Screen tips, Buzzer
Email Alarm	Send Image to The Designated E-mail
PTZ	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
Display	
VGA	resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
HDMI	resolution: 3840×2160/30Hz, 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
Display Split	32 Channel/25 Channel/16 Channel/9 Channel/8 Channel/4 Channel / 1Channel
Privacy Masking	1 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording	
Video Compression	H.264
Audio Compression	G.711u
Resolution	Half 1080P(960×1080);720P(1280×720);960H(P:960×576/N:960×480)
Video Quality	worst/worse/ordinary/well/best
Record Rate	Analog: PAL:Half 1080P(960×1080 32*12fps),720P(1280×720 32*15fps), 960H(960×576 32*25fps) NTSC:Half 1080P(960×1080 32*15fps),720P(1280×720 32*15fps), 960H(960×480 32*30fps) Pure IP: PAL :4k@13×25fps,5MP@15×25fps,4MP@22×25fps,3MP@22×25fps,1080P@32×25fps, 960P@32×25fps,720P@32×25fps, D1@32×25fps NTSC: 4k@13×30fps,5MP@15×30fps,4MP@22×30fps,3MP@22×30fps,1080P@32×30fps, 960P@32×30fps, 720P@32×30fps, D1@32×30fps
Record Mode	Manual\Timer\Motion Detection\alarm
Playback & Backup	
Decode Capability	4CH 5MP@30fps
Sync Playback	Pure Analog: 32CH 1080N@12fps Mixture Mode: 4CH 1080P@30fps, 4CH 1080N@12fps Pure Network: 10CH 1080P@30fps, 4CH 5MP@30fps , 2CH 8MP@30fps
Remote Playback	4 Channel / 1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind
Smart Phone Playback	4 Channel
Backup Mode	USB Device/Network
Network	
Interface	1 RJ45 10M/100M/1000M Adaptive Ethernet Interface
Network Functions	HTTP, IPv4,IPv6, TCP/IP, SMTP, DHCP, DNS, PPPOE, DDNS, NTP, FTP, UPNP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES
Web Browser	IE8-11, Google Chrome (IE Tab), Firefox (IE Tab)
CMS Software	Support Windows XP /Windows Vista/Windows 7/Windows 8
Extra Stream	CIF(1~15fps)
Smart Phone	iPhone, ipad, Android ,Android pad
Hard Disk Driver	
Interface Type	8 SATA Interface
Capacity	8 SATA Hard Disk Interface (3.5" SATA, Up to 48TB) + 1 E-SATA Interface (Up to 6TB)
General	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turcic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	AC 115~230v ≤35W (Without HDD)
Working Environment	-10~55°C/10~90%
Dimension (W×D×H)	440*450*95(mm)
Weight	9.8kg (Without HDD)